



SPREADER EQUIPMENT

EMDEK SUBSOIL FERTILIZER APPLICATOR



Heavy duty tine mounted with forged reversible steel point for max. soil penetration



Adjustable mouldboard to cover back soil



Adjustable roller height to re-compact soil

MODEL	SB300	SB500
Hopper Capacity, lit	300	500
Hopper Material	Fibreglass	
Working Depth, inch	1 - 7	
Spreading Productivity, ha/day	≤ 20	
Tractor horsepower Required, hp	40 - 95	50 - 95
Max Tractor PTO, RPM	540	
PTO Drive Shaft	T10 Drive Shaft	
Tractor Linkage Category	Cat I&II	
Dimension, mm (L x W x H)	1,092 x 1,194 x 1,416	1,092 x 1,194 x 1,646
Weight, kg	± 183	± 189

EMDEK SULPHUR DUSTER ATTACHMENT



FEATURES

- A stainless steel extension chute on side of the machine to convert it to blow Sulphur in rubber areas to combat *Oidium* problem.
- Comes with a closing cover for the other discharge chute opening



Extension chute suitable for any fertilizer spreader model (300/500/650 & 850 lit.)



Height of blow : 10 - 15 m



Closing cover for the other chute

Distributor



PT. SAHABAT AGRITAMA

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3 Gn. Sahari Utara. Kecamatan Sawah Besar, Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

Informasi



(021) 6594011



082 125 406 086



sahabatagritama@sahabatgroup.com



www.sahabatagritama.com