



SPRAYING EQUIPMENT

EMDEK EMD 15 CANNON AIR BLAST SPRAYER



Double Spout



Triple Spout

- For use in tall oil palm areas specially for bag worms and other pest and diseases
- Using Hydraulic control or Electric Motor (12V) to blast liquid droplet in 180° left or right to ensure maximum spraying coverage



MODEL	600	800
Tank Capacity, lit	600	800
Tank Material	Strong Polyethylene (PE) with UV Protection	
Spraying Height, m	15 – 20	
Spraying productivity, ha/day	20 – 25	
Fan Turbine Speed	High Speed Turbine Fan, can reach 2,430 rpm with air volume 20,000 m ³ /hr	
Max. Pump Pressure, bar	40	
Pump Discharge Rate, L/min	45	
Tractor horsepower Required, hp	60-95	
Max Tractor PTO, RPM	540	
PTO Drive Shaft	T60 Drive Shaft	
Tractor Linkage Category	Cat I & II	
Dimension, cm (L x W x H)	167.6 x 160.0 x 175.3	167.6 x 175.3 x 188.0
Weight, kg	± 300	± 317



Pressure control units made from Italy



Diaphragm pump made from Italy



Suction hose to draw water from external source



PTO Drive Shaft



2-speed for gearbox: 1:3.5, Neutral & 1:4.5



Hand Valve Control

Distributor

PT. SAHABAT AGRITAMA

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3 Gn. Sahari Utara. Kecamatan Sawah Besar, Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

Informasi

- ☎ (021) 6594011
- ☎ 082 125 406 086
- ✉ sahabatagritama@sahabatgroup.com
- 🌐 www.sahabatagritama.com