



COMPOSTING EQUIPMENT

EMDEK COMPOST APPLICATOR



MODEL	3 CBM	5 CBM
Hopper Capacity	3 CBM	5 CBM
Max. Load Approx. (Kg.)	Approx. 1,500 kg depending on the type and density of material used.	Approx. 2,500 kg depending on the type & density of material used
Type of Hopper	Mild steel	
Shape of Hopper	"U" shaped	
Effective Discharge	Single sided on the left hand side. Application is through a high speed rotor fitted with swing blades	
Effective Spreading Width, m	8-10 m approx.	8 – 12 m approx.
Hydraulically Operated	The deflector and discharge door are operated by hydraulic rams	
PTO RPM	540	
Tractor PTO	Suitable for tractor PTO shafts with 6 splines 1 3/8" diameter	
Tractor HP	70 HP and above	
Tractor Linkage	None, Trailed unit require tractor drawbar	
Construction Material Used	Hopper and chassis are of heavy gauged mild steel.	
Gearbox & Lubrication	Fabricated steel chain cases lubricated with grease and engine oil. Gears and Sprockets used are heavy duty and high load chains case requires 54Lit of engine oil of SAE140 rating.	
Clutch & PTO	Heavy duty PTO shaft with shearbolt clutch.	
Axle & Wheels	3 ton axle with 750 x 16" twin wheel retread tyres	6 tons axle 9.0 x 20" twin wheel retread tyres
Size	L: 168" x H: 70" x W: 78"	L: 168" x H: 82" x W: 90"

Distributor

 **PT. SAHABAT AGRITAMA**

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3 Gn. Sahari Utara. Kecamatan Sawah Besar, Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

Informasi

 (021) 6594011
 082 125 406 086
 sahabatagritama@sahabatgroup.com
 www.sahabatagritama.com