

ROTAVATOR | B-26

Model	B26	155	180	205
Dimension, mm (L x W x H)		1805 x 1025 x 1060	2060 x 1025 x 1060	2315 x 1025 x 1060
Working Width, cm		155	180	205
For Tractor, Hp		45-60hp	55-75hp	70-80Hp
3-Point Linkage, CAT		I/II		
Universal Driveshaft		A6 c/w FF2 Slip Clutch		
Gearbox		Multi Speed		
No of Flanges		7	8	9
No of Blades		36	42	48
Size of Blades, mm		75 x 6		
Rotor Speed at 540 rpm		158 / 176 / 221 / 247		
Side Transmission Drive		Rollerchain & Sprocket		
Max Working Depth, cm		16		
Type of Blade		C or L (Optional)		
Weight (kg)		470	510	550

L / C Blade



Face Seal



Gearbox



PTO Drive Shaft



Model B-26 requires min. 45 hp and is designed for general soil preparation in wet or dry-land conditions. With multispeed gear-settings, B-26 provides a wide choice of tillage - to suit crop, soil and climate. Powerful transmission with inbuilt safety features to protect machine and tractor against shock-loads.

A popular workhorse for contractors, its many features are neatly incorporated in a simple design - userfriendly and easy to maintain. All models come with metal to metal face seals to prevent water from contaminating transmission oil when working in wet



Distributor

 **PT. SAHABAT AGRITAMA**

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3 Gn. Sahari Utara. Kecamatan Sawah Besar, Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

Informasi

☎ (021) 6594011
 ☎ 082 125 406 086
 ✉ sahabatagritama@sahabatgroup.com
 🌐 www.sahabatagritama.com