

ROTAVATOR | B-36



Model	B36	155	180	205	230	255
Dimension, mm (L x W x H)		1805 x 1025 x 1100	2060 x 1025 x 1100	2315 x 1025 x 1100	2570 x 1025 x 1100	2825 x 1025 x 1100
Working Width, cm		155	180	205	230	255
For Tractor, Hp		55-60hp	60-75hp	70-90hp	90-110hp	90-110hp
3-Point Linkage, CAT		I/II				
Universal Driveshaft		A8 c/w FF4 Slip Clutch				
Gearbox		Multi Speed				
No of Flanges		7	8	9	10	11
No of Blades		36	42	48	54	60
Size of Blades, mm		80 x 7				
Rotor Speed at 540 rpm		166 / 203 / 144 / 235				
Side Transmission Drive		Rollerchain & Sprocket				
Max Working Depth, cm		18				
Type of Blade		L or C (Optional)				
Weight (kg)		470	510	550	590	630

L / C Blade



Face Seal



Multi Speed Gear

PTO Drive Shaft



This extra-heavy-duty rotavator performs excellently in demanding conditions and is ideal for "built-on" combinations - such as Ripper, Furrower or Crumble Roller.

Side drive through heavy-duty Roller Chain - 17 ton breaking load - with externally adjustable tensioning skid. Rotor drive is supported by large ball bearings and face seals.

Protection of tractor and transmission against shock-loads ensured by heavy - duty safety clutch.

Cultivating depth is adjustable - raising-lowering the side skids.

Depth control wheels available as optional.

Selectatilt pick- off gears allow four alternative rotor speeds (540 PTO)



Distributor

 **PT. SAHABAT AGRITAMA**

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3 Gn. Sahari Utara. Kecamatan Sawah Besar, Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

Informasi

 (021) 6594011

 082 125 406 086

 sahabatagritama@sahabatgroup.com

 www.sahabatagritama.com