



Easy access swing-out centre unit



Automatic Hill Hold Parking Brake



Programmable frequency of cut

REELS & BLADES

NUMBER AND SIZE	3 x 22" (55.88cm) reels; 5" (12.7cm) diameter
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	New Long Life linear actuator
CUTTING FREQUENCY	0.036" - 0.250" (0.91 mm - 6.35 mm) with 15 blade reel, electronically adjustable

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Front / 2WD - AC; 4.4HP (3.3kW) continuous (Optional 3WD - PM; 3.2HP (2.4kW))
REEL DRIVE	One brushless DC motor per reel; 1.3HP (0.97kW) continuous
HYDRAULIC SYSTEM	No hydraulic oil
SERVICE BRAKES	Dynamic regenerative braking system
PARKING BRAKES	Automatic electro-magnetic multi-plate
STEERING	Variable ratio Drive-by-wire steering with feedback control
MOWING SPEED	0 - 5.0mph (0 - 8.9kph); electronically adjustable max speed
TRANSPORT SPEED	0 - 9.0mph (0 - 14.5kph); electronically adjustable max speed

WEIGHTS & DIMENSIONS

	HYBRID GASOLINE	HYBRID DIESEL
WEIGHT (excluding fuel)	1322lbs (599kg) with all fluids	1362lbs (618kg) with all fluids
LENGTH	101" (2.56m) with catchers	
OVERALL HEIGHT (including ROPS)	79.3" (2.01m)	
WHEELBASE	52" (1.32m)	
TRANSPORT WIDTH	67.7" (1.72m)	
WORKING WIDTH	67.7" (1.72m)	

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ROLLERS

- 22" (55.9 cm) Grooved assembly steel disk roller - 2" (5.1 cm) dia.
- 22" (55.9 cm) Grooved segmented machined aluminum roller - 2 1/4" (5.7 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (light duty) - 2" (5.1 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (heavy duty) - 2" (5.1 cm) dia.
- 22" (55.9 cm) Grooved machined steel roller - 2 1/4" (5.6 cm) dia.
- 22" (55.9 cm) Grooved machined aluminum roller - 2 1/4" (5.6 cm) dia.



ACCESSORIES

- Turf Groomer: 22" (55.9 cm) width and 0.25" (6.3mm) or 0.50" (12.7mm) spacing
- Spiker
- Powered rear roller cleaning brush
- High cut kit - 15/16" 2.4 cm when used with 2 3/16" roller
- Premium seat - grammar seat in grey vinyl with suspension base, adjustable brackets
- ROPS mounted LED light kit
- Dew whip holder
- Canopy / sunshade kit - adjustable
- Tow bar
- Traction tire assembly 18 x 9.5 x 8 (wheel and tire)
- Turf brushing groomer
- Bi-directional groomers and brushes 3WD kit

Distributor

PT. SAHABAT AGRITAMA

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3 Gn. Sahari Utara. Kecamatan Sawah Besar, Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

Informasi

- ☎ (021) 6594011
- ☎ 082 125 406 086
- ✉ sahabatagritama@sahabatgroup.com
- 🌐 www.sahabatagritama.com



ROPS as standard

Hybrid Gas - Briggs & Stratton® 13.3HP (9.92kW)
Air cooled V twin gasoline
Hybrid diesel - Kubota® 13.3HP (9.92kW) diesel

Steer-by-wire system means no hydraulics and cables

Onboard diagnostics screen & backlapping

LED Light

Unique independent cutting unit lift and lower system

Jake's Signature 22" (55.9cm) 7, 9, 11 & 15 blade reels or optional 22" (55.9cm) Verticut 7.5" (19mm) reel

Optional 2 or 3 WD

Regenerative braking with automatic parking brake

New cutting unit lift features a low wearing brushless DC linear actuator



Easy access swing-out centre unit



Automatic Hill Hold Parking Brake



Programmable frequency of cut

REELS & BLADES

NUMBER AND SIZE	3 x 22" (55.88cm) reels; 5" (12.7cm) diameter
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	New Long Life linear actuator
CUTTING FREQUENCY	0.036" - 0.250" (0.91 mm - 6.35 mm) with 15 blade reel, electronically adjustable

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Front / 2WD - AC; 4.4HP (3.3kW) continuous (Optional 3WD - PM; 3.2HP (2.4kW))
REEL DRIVE	One brushless DC motor per reel; 1.3HP (0.97kW) continuous
HYDRAULIC SYSTEM	No hydraulic oil
SERVICE BRAKES	Dynamic regenerative braking system
PARKING BRAKES	Automatic electro-magnetic multi-plate
STEERING	Variable ratio Drive-by-wire steering with feedback control
MOWING SPEED	0 - 5.0mph (0 - 8.9kph); electronically adjustable max speed
TRANSPORT SPEED	0 - 9.0mph (0 - 14.5kph); electronically adjustable max speed

WEIGHTS & DIMENSIONS

	HYBRID GASOLINE	HYBRID DIESEL
WEIGHT (excluding fuel)	1322lbs (599kg) with all fluids	1362lbs (618kg) with all fluids
LENGTH	101" (2.56m) with catchers	
OVERALL HEIGHT (including ROPS)	79.3" (2.01m)	
WHEELBASE	52" (1.32m)	
TRANSPORT WIDTH	67.7" (1.72m)	
WORKING WIDTH	67.7" (1.72m)	

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ROLLERS

- 22" (55.9 cm) Grooved assembly steel disk roller - 2" (5.1 cm) dia.
- 22" (55.9 cm) Grooved segmented machined aluminum roller - 2 1/4" (5.7 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (light duty) - 2" (5.1 cm) dia.
- 22" (55.9 cm) Solid tube steel roller with scraper (heavy duty) - 2" (5.1 cm) dia.
- 22" (55.9 cm) Grooved machined steel roller - 2 1/4" (5.6 cm) dia.
- 22" (55.9 cm) Grooved machined aluminum roller - 2 1/4" (5.6 cm) dia.



ACCESSORIES

- Turf Groomer: 22" (55.9 cm) width and 0.25" (6.3mm) or 0.50" (12.7mm) spacing
- Spiker
- Powered rear roller cleaning brush
- High cut kit - 15/16" 2.4 cm when used with 2 3/16" roller
- Premium seat - grammar seat in grey vinyl with suspension base, adjustable brackets
- ROPS mounted LED light kit
- Dew whip holder
- Canopy / sunshade kit - adjustable
- Tow bar
- Traction tire assembly 18 x 9.5 x 8 (wheel and tire)
- Turf brushing groomer
- Bi-directional groomers and brushes 3WD kit

Distributor

PT. SAHABAT AGRITAMA

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3 Gn. Sahari Utara. Kecamatan Sawah Besar, Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

Informasi

- ☎ (021) 6594011
- ☎ 082 125 406 086
- ✉ sahabatagritama@sahabatgroup.com
- 🌐 www.sahabatagritama.com