

GREENS KING® IV PLUS



SIMPLY DELIVERS TRUSTED PERFORMANCE

The Greens King IV Plus is a trusted and proven riding greens mower that offers superior quality of cut every time. The Greens King IV Plus, available in both gas and diesel models, features power steering for easy operation and additional horsepower to tackle harder jobs. All Greens King models feature a lightweight, simple design that is gentle on turf and easy to maintain.

.062 - .438"
HEIGHT OF CUT

**GAS
OR
DIESEL**

3.7 MPH
MOW SPEED

62"
WIDTH OF CUT



GREENS KING IV PLUS

JACOBSEN® ADVANTAGE

For over 95 years, Jacobsen has been designing and manufacturing industry-leading turf maintenance equipment. A strong focus on engineering innovative technology has led to advancements that deliver impeccable quality of cut on user-friendly equipment.



EQUIPPED AS STANDARD

- Greenscare Biodegradable Oil
- On-Board Backlapping
- Walk-Through Operator Station
- Free-Floating, Steerable Tractor Heads

OPTIONS

- Vertical Mowers
- Spikers
- Brushes
- Greens rollers
- Turf Groomers® for 3D Mowing
- Full Lineup of Accessories

ENGINE	GAS	DIESEL
TYPE	Briggs & Stratton® Vanguard™ V-twin	Kubota® D722 3-cylinder Tier 4 Gas; Briggs & Stratton® Vanguard™ V-twin
HORSEPOWER*	18 hp (13.4 kW) @3600 rpm	17.7 hp (13.2 kW)
DISPLACEMENT	34.78 cu. in. (570 cc) @3600 rpm	43.88 cu. in. (719 cc)
AIR CLEANER SYSTEM	Dual Element	Dry, two stage
COOLING SYSTEM	Air cooled	Pressurized, sealed cooling system; coolant capacity: 3 qt. (2.85 L)
FUEL CAPACITY	8 gal. (31 L)	8 gal. (31 L)
TRACTION & DRIVE		
TRACTION DRIVE	Hydraulic motor on each drive wheel	
REEL DRIVE	Gear-type hydraulic motor; backlap control valve standard	
REEL LIFT HYDRAULIC SYSTEM	Hydraulic double action cylinders; 5 gal. (18.9 L) capacity; 20-micron, full flow filtration; biodegradable fluid	
SPEED (MAXIMUM)		
MOWING	3.7 mph (6 km/h)	
TRANSPORT	6.6 mph (10.6 km/h)	
REVERSE	3.5 mph (5.6 km/h)	
TIRES, BRAKES & STEERING		
TIRES	18 x 9.5 - 8, 2-ply, pneumatic, tubeless	
PARKING BRAKE	Internal expanding, hand operated	
GROUND PRESSURE	10 psi (0.7 kg/cm ²)	
STEERING	Power	
REELS & BLADES		
NUMBER & SIZE	Three 22 in. (56 cm) reels; 5 in. (12.7 cm) diameter	
NUMBER OF BLADES	7, 9, 11	
BLADE MATERIAL	Hardened, high-carbon steel	
CUTTING FREQUENCY	0.053 in./mph (0.836 mm/kph) with 11 blade reels, 0.035 in./mph (0.889 mm/kph) with 5 blade reels	
OVERALL CUTTING WIDTH	62 in. (1.6 m)	
HEIGHT-OF-CUT RANGE**	0.062 - 0.438 in. (1.6 - 11.1 mm)	
WEIGHT & DIMENSIONS		
WEIGHT	GK IV Plus Gas: 1073 lbs. (486.7 kg)	GK IV Plus Diesel: 1174 lbs (532.5 kg)
LENGTH (less catchers)	87.5 in. (2.22 m)	
HEIGHT (with ROPS)	78 in. (1.98 m)	
WHEELBASE	51.5 in. (1.34 m)	
WIDTH	70 in. (1.78 m) in mow mode; 50.5 in. (1.27 m) in transport mode	

* Engine power is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.
 ** Height of cut depends on turf condition, reel wear and bedknife installed.

NOTE: Specifications, while correct at time of printing, may change without notice.

Distributor



PT. SAHABAT AGRITAMA

(021) 6594011

www.sahabatagritama.com

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3

Gn. Sahari Utara. Kecamatan Sawah Besar

Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720