

AR530

ARTICULATED CONTOUR ROTARY MOWER

JACOBSEN



- **TRUEDECK™ HEAVY-DUTY CONTOUR DECK**
- **SUPERIOR AFTER-CUT APPEARANCE**
- **QUICK AND EASY DECK ADJUSTMENT**
- **TRUSTWORTHY KUBOTA ENGINE**
- **EXCEPTIONAL HILL CLIMBING AND SIDE SLOPE PERFORMANCE**

Redesigned from the ground up, the AR530 contour rotary mower is built to give you the best.

Designed with TRUEDECK™ heavy duty contour decks, that deliver superior cut quality and after cut appearance, the AR530 was built to provide outstanding performance on hills, slopes and contours.

The AR530 offers an easy to read full color operator interface, premium air ride seat and reversing fan all as Standard.

CUT WIDTH 90" (2.3M)	CUT HEIGHT 0.75" - 4.5" (19MM - 114MM) 0.25" (6MM) INCREMENTS	CUTTING CAPACITY 5.66 AC UP TO (2.29HA) / HR AT 7MPH (11.26KPH)
FUEL CAPACITY 17 GAL (64.2L)	ENGINE KUBOTA® 50.2 HP (37.4KW) DIESEL	TRANSPORT SPEED 12 MPH (19.3KPH)



SINCERELY

Take



Distributor

PT. SAHABAT AGRITAMA

(021) 6594011

www.sahabatagritama.com

Alamat: No. 1. Blok B1 - B2 Jl. Gn. Sahari RT.16/RW. 3

Gn. Sahari Utara. Kecamatan Sawah Besar

Kota Jakarta Pusat, Daerah Khusus Ibukota Jakarta 10720

AR530

ARTICULATED CONTOUR ROTARY MOWER



Full colour LCD operator screen with machine diagnostics

Premium air ride suspension seat on every unit - work all day in comfort.

Foldable ROPS

Improved operator environment; ease of access, optimised seating position, adjustable steering wheel

Programmable performance setting allows you to be in control of transport, mow and turn speeds

Maintenance-free, wet parking brakes

Hydraulic hood struts for worry free access and convenience

Reversing fan as standard



Vertical lift on outside decks for manoeuvrability



50.2 HP (37.4 kW) diesel Kubota® engine



TRUEDECK™ heavy-duty cutting decks

90" (2.3m) cutting width

Jake's best traction that meets your application

Decks specifically designed for cut performance and after-cut appearance

DECKS & CUTTING UNITS

NUMBER AND SIZE	5 x TRUEDECK™ 23" (58.4cm) rotary cutting units. Equipped for rear-discharge chute and smooth rear roller. Mulching baffle, non-stripping rear roller and rear roller scrapers available
BLADE MATERIAL	5 x 22.4" (56.8cm) heat treated alloy combo blades
DECK LIFT & LOWER	Hand operated, joystick controlled hydraulic lift system
WEIGHT TRANSFER	Adjustable hydraulic weight transfer – automatic electronic activation at operator controls with mow switch. Selectable through control console
DECK CONSTRUCTION	10-gauge, heavy duty modular deck construction

TRACTION, BRAKES & SPEED

TRACTION DRIVE	SureTrac II™ AWD, a unique parallel hydrostatic system, servo-controlled variable displacement hydro; four high-torque wheel motors; 2WD transport and reverse
DECK DRIVE	Fixed displacement, self-lubricating with 1" (2.54cm) diameter shaft; double sealed bearings
HYDRAULIC SYSTEM	10 gal. (37.9L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter, 40 gpm. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic through traction system
PARKING BRAKES	Maintenance-free, integrated wet parking brake; front wheel motors; engage switch on control console
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	7mph (11.3kph)
REVERSE SPEED	5mph (8kph)

WEIGHTS & DIMENSIONS

WEIGHT	3451 lb. (1565 kg) full fluids
LENGTH	137.5" (3.49m)
OVERALL HEIGHT	91.6" (2.326m) ROPS up, 71.5" (1.81m) ROPS folded
WHEELBASE	63" (1.6m)
TRANSPORT WIDTH	88.6" (2.25m)
WORKING WIDTH	95.3" (2.42m)

ACCESSORIES

■ 692771 Blade 23" Hi-lift	■ 677080 Kit - quick release pin, 5 gang	■ 698270 Roller - service 76 x 567 grooved polymer
■ 692774 Blade 23" combo	■ 677092 Kit - mulching, 23"	■ 698272 Roller - service 76 x 567 solid polymer
■ 692775 Blade 23" mulch	■ 677261 Kit - quick release pin, 7 gang	■ 4394939 Acc, cargo net
■ 68127 Canopy kit	■ 689563 Kit - 23" cable scraper	■ 10002064 Kit - 23" grooved roller scraper